

# WET WELL MONITOR MARK II

## METHANE · OXYGEN · HYDROGEN SULFIDE

For Hazardous Wastewater Environments

System includes three remote 4-20mA/24 VDC sensor/transmitters in explosionproof Class I, Div I, Group B, C, D enclosures. Specifically designed to monitor CH<sub>4</sub>, H<sub>2</sub>S, & O<sub>2</sub>.

### Monitor Features

- Digital Display
- User-Programmable Alarms
- 2 Alarm Levels per Channel
- Audio/Visual Alarms
- 5 Alarm Relays, plus 1 Fault Relay
- 100-240 VAC, 24 VDC Power Options
- Provides 24 VDC Loop Power
- Designed for 24 VDC Battery Backup
- High-Capacity User-Programmable Relays
- High-Integrity Thermoplastic Enclosure
- 4-20 mA Output per Channel
- RS-485 Digital Communication Capability



### Sensor/Transmitter Features

- Digital Display
- Non-invasive Calibration
- Explosionproof Sensor/Transmitters
- Magnetically Activated Calibration/Programming Switches
- Alarm LEDS
- Optional Relay PCB



H<sub>2</sub>S  
Sensor



Methane  
Sensor



Oxygen  
Sensor



Specifications subject to change without notice